



SSUCF 200A 系列

带座轴承 型号	轴 径		基本尺寸(mm)									螺栓 尺寸 (mm)	重量 (kg)
	d		L	J	A ₂	A ₁	A	N	Z	B	S		
	(in)	(mm)											
SSUCF204A 204-12A	3/4	20	86	64	15	11	25.5	12	33.3	31	12.7	M10	0.71
SSUCF205A 205-14A 205-15A 205-16A	7/8 15/16 1	25	95	70	16	13	28	12	35.8	34.1	14.3	M10	0.97
SSUCF206A 206-17A 206-18A 206-19A 206-20A	1-1/16 1-1/8 1-3/16 1-1/4	30	108	83	18	13	31	12	40.2	38.1	15.9	M10	1.41
SSUCF207A 207-20A 207-21A 207-22A 207-23A	1-1/4 1-5/16 1-3/8 1-7/16	35	117	92	19	15	34	14	44.4	42.9	17.5	M12	1.86
SSUCF208A 208-24A 208-25A	1-1/2 1-9/16	40	130	102	21	15	36	16	51.2	49.2	19	M14	2.30
SSUCF209A 209-26A 209-27A 209-28A	1-5/8 1-11/16 1-3/4	45	137	105	22	16	38	16	52.2	49.2	19	M14	2.71
SSUCF210A 210-30A 210-31A 210-32A	1-7/8 1-15/16 2	50	143	111	22	16	40	16	54.6	51.6	19	M14	2.93
SSUCF211A 211-32A 211-34A 211-35A	2 2-1/8 2-3/16	55	162	130	25	18	43	19	58.4	55.6	22.2	M16	4.13
SSUCF212A 212-36A 212-38A 212-39A	2-1/4 2-3/8 2-7/16	60	175	143	29	18	48	19	68.7	65.1	25.4	M16	5.51

备注: (1) 可选配通盖或盲盖(OC/CC)。(2) 可选配后油封。
(3) 不锈钢座表面可手工抛光处理, 例如: SSUCF204-12A-HP