



SSUCP 200A 系列

带座轴承型号	轴 径	基本尺寸(mm)											螺栓 尺寸 (mm)	重量 (kg)
		d (in)	H	L	J	A	N	N ₁	H ₁	H ₀	B	S		
SSUCP204A 204-12A	20	3/4	33.3	127	95	30	13	19	14	64	31	12.7	M10	0.71
SSUCP205A 205-14A 205-15A 205-16A	25	7/8 15/16 1	36.5	140	105	30	13	19	15	70	34.1	14.3	M10	0.82
SSUCP206A 206-17A 206-18A 206-19A 206-20A	30	1-1/16 1-1/8 1-3/16 1-1/4	42.9	165	121	36	17	21	16	82	38.1	15.9	M12	1.31
SSUCP207A 207-20A 207-21A 207-22A 207-23A	35	1-1/4 1-5/16 1-3/8 1-7/16	47.6	167	127	38	17	21	17	92	42.9	17.5	M12	1.65
SSUCP208A 208-24A 208-25A	40	1-1/2 1-9/16	49.2	184	137	40	17	21	18	98	49.2	19	M12	2.00
SSUCP209A 209-26A 209-27A 209-28A	45	1-5/8 1-11/16 1-3/4	54	190	146	40	17	21	20	105	49.2	19	M12	2.26
SSUCP210A 210-30A 210-31A 210-32A	50	1-7/8 1-15/16 2	57.2	206	159	45	20	22	22	112	51.6	19	M16	2.80
SSUCP211A 211-32A 211-34A 211-35A	55	2 2-1/8 2-3/16	63.5	218	171	50	20	22	22	126	55.6	22.2	M16	3.83
SSUCP212A 212-36A 212-38A 212-39A	60	2-1/4 2-3/8 2-7/16	69.9	238	184	60	20	25	25	137	65.1	25.4	M16	5.33

备注: 1、油嘴位置有90°和45°可选择。

2、可选配通盖或盲盖(OC/CC)。

3、不锈钢座表面可手工抛光处理, 例如:SSUCP204-12 A-HP