



SB200
带顶丝外球面球轴承



CSB200
带顶丝外圆柱面球轴承



SB200G
可再润滑型



H型密封



J型密封

SB200 CSB200 系列

轴承 型号	轴 径		基本尺寸(mm)								基本额定载荷 (N)			重量 (kg)
	d		D	B	C	S	S ₁	G	ds		Ca	动载荷 C _r	静载荷 C _{0r}	
	(in)	(mm)							(mm)	(in. UNF)				
SB 201		12	40	22	12	6.0	16.0	4.9	M5x0.8	10-32	3.5	9550	4780	0.09
SB 201-8	1/2	15	40	22	12	6.0	16.0	4.9	M5x0.8	10-32	3.5	9550	4780	0.08
SB 202-9	9/16	17	40	22	12	6.0	16.0	4.9	M5x0.8	10-32	3.5	9550	4780	0.07
SB 202-10	5/8	20	47	25	14	7.0	18.0	5.0	M6x1	1/4-28	4	12620	6650	0.12
SB 203-11	11/16	25	52	27	15	7.5	19.5	5.5	M6x1	1/4-28	4.3	14030	8050	0.18
SB 204-12	3/4	30	62	30	16	8.0	22.0	5.9	M6x1	1/4-28	4.9	19470	11430	0.26
SB 205-13	13/16	35	72	32	17	8.5	23.5	8.0	M8x1	5/16-24	5.5	25690	15550	0.43
SB 205-14	7/8													
SB 205-15	15/16													
SB 205-16	1													
SB 206-17	1-1/16	40	80	34	18	9	25.0	8.0	M8x1	5/16-24	6.0	29510	18140	0.60
SB 206-18	1-1/8	45	85	36	19	9.5	31	8.0	M8x1	5/16-24	6.1	31850	20800	0.80
SB 206-19	1-3/16													
SB 206-20	1-1/4													
SB 207	1-1/4													
SB 207-20	1-5/16	50	90	38	20	10	32.6	10.0	M10x1.25	3/8-24	6.6	34990	23700	0.83
SB 207-21	1-1/8													
SB 207-22	1-3/8													
SB 207-23	1-7/16													
SB 208-24	1-1/2	55□	100	40	21	10.5	32.6	10.0	M10x1.25	3/8-24	7.2	43340	29390	1.12
SB 208-25	1-9/16													
SB 209	1-5/8													
SB 209-26	1-11/16													
SB 209-27	1-3/4	60□	110	42	22	11	32.6	10.0	M10x1.25	3/8-24	7.5	47680	33430	1.55
SB 210	1-7/8													
SB 210-30	1-15/16													
SB 210-31	2													
SB 210-32	2	60□	110	42	22	11	32.6	10.0	M10x1.25	3/8-24	7.5	47680	33430	1.55
SB 211	2													
SB 211-32	2-1/16													
SB 211-33	2-1/8													
SB 211-34	2-3/16	60□	110	42	22	11	32.6	10.0	M10x1.25	3/8-24	7.5	47680	33430	1.55
SB 211-35	2-3/16													
SB 212	2-1/4													
SB 212-36	2-5/16													
SB 212-37	2-3/8	60□	110	42	22	11	32.6	10.0	M10x1.25	3/8-24	7.5	47680	33430	1.55
SB 212-38	2-7/16													
SB 212-39	2-7/16													
SB 212-40	2-7/16													

备注: 1) 后缀G=外圈带油槽和油孔。

2) 后缀N=非润滑型, 不带油槽和油孔, 不带定位钉和定位钉孔。