



NAP200 系列

带座轴承 型号	轴 径		基本尺寸(mm)										螺栓 尺寸 (mm)	重量 (kg)
	d (in)	d (mm)	H	L	J	A	N	N ₁	H ₁	H ₀	B ₁	S		
NAP 201		12	30.2	127	95	38	13	19	14	61	43.7	17.1	M10	0.72
201-8	1/2													
202		15	30.2	127	95	38	13	19	14	61	43.7	17.1	M10	0.72
202-9	9/16													
202-10	5/8													
203		17	30.2	127	95	38	13	19	14	61	43.7	17.1	M10	0.72
203-11	11/16													
NAP 204		20	33.3	127	95	38	13	19	14	64	43.7	17.1	M10	0.72
204-12	3/4													
NAP 205		25	36.5	140	105	38	13	19	15	71	44.4	17.5	M10	0.8
205-14	7/8													
205-15	15/16													
205-16	1													
NAP 206		30	42.9	160	121	44	17	21	16	82	48.4	18.3	M14	1.35
206-18	1-1/16													
206-19	1-1/8													
206-20	1-3/16													
206-20	1-1/4													
NAP 207		35	47.6	167	126	48	17	21	17	92	51.1	18.8	M14	1.7
207-20	1-1/4													
207-21	1-5/16													
207-22	1-3/8													
207-23	1-7/16													
NAP 208		40	49.2	180	137	52	17	21	18	99	56.3	21.4	M14	2
208-24	1-1/2													
208-25	1-9/16													
NAP 209		45	54	190	146	54	17	21	20	106	56.3	21.4	M14	2.42
209-26	1-5/8													
209-27	1-11/16													
209-28	1-3/4													
NAP 210		50	57.2	206	159	60	20	25	21	114	62.7	24.6	M16	2.75
210-30	1-7/8													
210-31	1-15/16													
210-32	2													
NAP 211		55	63.5	218	172	60	20	25	23	125	71.4	27.8	M16	3.56
211-32	2													
211-34	2-1/8													
211-35	2-3/16													
NAP 212		60	69.9	238	186	70	20	25	25	137	77.8	31	M16	5.2
212-36	2-1/4													
212-38	2-3/8													
212-39	2-7/16													
NAP 213		65	76.2	262	203	70	25	30	26	149	85.7	34.3	M20	6.3
213-40	2-1/2													
NAP 214		70	79.4	266	210	72	25	30	28	157	85.7	34.3	M20	7
214-44	2-3/4													
NAP 215		75	82.6	274	217	74	25	30	28	159	92.1	37.3	M20	7.8
215-47	2-15/16													
215-48	3													

备注：1、油嘴位置有90° 和45° 可选择。