


UCX00

帶頂絲外球面球軸承



UCX00G
可再潤滑型



SL型密封



TJ型密封



L3型密封

UCX00 UCX00L3 系列

轴承 型号	轴 径		基本尺寸(mm)								额定动载 荷 (N)	额定静载 荷 (N)	重量 (kg)	
			D	B	C	S	S ₁	G	ds					Ca
	(mm)	(in. UNF)												
UCX 05 05-13 05-14 05-15 05-16	13/16 7/8 15/16 1	25	62	38.1	19	15.9	22.2	5.5	M6X1	1/4-28	5.3	19470	11430	0.39
UCX 06 06-17 06-18 06-19 06-20	1-1/16 1-1/8 1-3/16 1-1/4	30	72	42.9	20	17.5	25.4	6.9	M8X1	5/16-24	5.8	25690	15550	0.68
UCX 07 07-21 07-22 07-23	1-5/16 1-3/8 1-7/16	35	80	49.2	21	19	30.2	8	M8X1	5/16-24	6.2	29510	18140	0.82
UCX 08 08-24 08-25	1-1/2 1-9/16	40	85	49.2	22	19	30.2	8	M8X1	5/16-24	6.5	31850	20800	0.93
UCX 09 09-26 09-27 09-28	1-5/8 1-11/16 1-3/4	45	90	51.6	24	19	32.6	10	M10X1.25	3/8-24	7	34990	23700	1.00
UCX10 10-30 10-31	1-7/8 1-15/16	50	100	55.6	25	22.2	33.4	10	M10X1.25	3/8-24	7.4	43340	29390	1.35
UCX11 11-33 11-34 11-35 11-36	2-1/16 2-1/8 2-3/8 2-1/2	55	110	65.1	27	25.4	39.7	10	M10X1.25	3/8-24	7.6	47680	33430	1.90
UCX12 12-38 12-39	2-3/8 2-7/16	60	120	65.1	28	25.4	39.7	10	M10X1.25	3/8-24	8.5	57200	40010	2.27
UCX13 13-40 13-41	2-1/2 2-9/16	65	125	74.6	29	30.2	44.4	12	M12X1.25	7/16-20	8.9	62190	43900	2.45
UCX14 14-42 14-43 14-44	2-3/8 2-11/16 2-3/4	70	130	77.8	30	33.3	44.5	12	M12X1.25	7/16-20	9.2	62080	44820	2.47
UCX15 15-45 15-46 15-47 15-48	2-13/16 2-7/8 2-15/16 3	75	140	82.6	33	33.3	49.3	12	M12X1.25	7/16-20	9.5	72620	53340	3.11
UCX16 16-49 16-50 16-51	3-1/16 3-1/8 3-3/16	80	150	85.7	35	34.1	51.6	12	M12X1.25	7/16-20	11.1	83150	64540	3.79
UCX17 17-53 17-55	3-5/16 3-7/16	85	160	96	37	39.7	56.3	12	M12X1.25	1/2-20	11.8	95840	72640	4.82