



LDK[®] 4-Bolt Flange Units

NAFS Standard duty, Wider inner ring bearing, Eccentric locking



Unit No.	Shaft Dia		Dimensions (mm)									Bolt Size (mm)	Weight (kg)
	d		L	J	A ₂	A ₁	A	N	B ₁	S	Z		
	(in)	(mm)											
NAFS 201S 201-8S 202S 202-10S 203S 203-11S	1/2 5/8 11/16	12 15 17	76	54	15	11	24.5	11.5	37.3	13.9	38.4	M10	0.66
NAFS 201 201-8 202 202-10 203 203-11 204 204-12	1/2 5/8 11/16 3/4	12 15 17 20	86	63.5	19	15	29.5	11.5	43.7	17	45.5	M10	0.8
NAFS 205 205-11 205-15 205-16	7/8 15/16 1	25	93	70	19	15	30	11.5	44.4	17.4	45.9	M10	0.95
NAFS 206 206-18 206-19 206-20	1-1/8 1-3/16 1-1/4	30	106	82.5	20	16	32.5	11.5	48.4	18.2	50.1	M10	1.32
NAFS 207 207-20 207-21 207-22 207-23	1-1/4 1-5/16 1-3/16 1-7/16	35	116	92	21	17	35	14	51.1	18.8	53.3	M12	1.77
NAFS 208 208-24 208-25	1-1/2 1-9/16	40	129	101.5	24	17	39	14	56.3	21.4	58.9	M12	2.22
NAFS 209 209-26 209-27 209-28	1-5/8 1-11/16 1-3/4	45	135	105	24	18	40	16	56.3	21.4	58.9	M14	2.63
NAFS 210 210-30 210-31 210-32	1-7/8 1-15/16 2	50	143	111	28	20	45	18	62.7	24.6	66.1	M16	2.95
NAFS 211 211-32 211-34 211-35	2 2-1/8 2-3/16	55	162	130	31	21	49	18	71.4	27.7	74.6	M16	4.10
NAFS 212 212-36 212-38 212-39	2-1/4 2-3/8 2-7/16	60	175	143	34	22	53.5	18	77.8	30.9	80.8	M16	4.86
NAFS 213 213-40	2-1/2	65	184	149	38	22	58	18	85.7	34.1	89.6	M16	5.90
NAFS 214 214-44	2-3/4	70	188	152	38	23	60	18	85.7	34.1	89.6	M16	6.45
NAFS 215 215-47 215-48	2-15/16 3	75	200	159	41	24	62	18	92.1	37.3	95.8	M16	7.55
NAFS 216		80	207	165	42	25	63	22	95.2	37.3	99.9	M20	8.65

Notes: Bearing housing solid base optional, add suffix SB as designation.