



带冲压座圆盘耙轴承分成209和211两个基本尺寸组。

它们具备了带座轴承的以下特征:

- ※ 自动调心功能 ($+3^\circ$).
- ※ 冲压紧游隙对内圈起到包压效果.
- ※ 可再润滑
- ※ 装配和装卸简单
- ※ 冲压座与轴承外圈采用过盈配合, 有效地防止轴承外圈圆周转动。

圆柱孔(RD)

正方形孔(SQ)

209 系列

轴承型号	类型	内径尺寸 (mm)		基本尺寸 (mm)									基本额定载荷 (N)											
		H (SQ)	d (RD)	L	P	B	A	F	do	E	C	N(N1XN2)	动载荷 Cr	静载荷 Cor										
ST491A	1	--	45	127	98	42.8	42	60	57.547	7	127	Ø13.5	31850	17500										
ST491A-I	2	--					37					13.5X16.7												
ST491A-II	3	--					42					Ø13.5												
DHU45R-209	1	--					37					13.5X16.7												
ST491B	1	--	38.86				127	98	42.8	42	60	57.547			7	127	Ø13.5	31850	17500					
ST491B-I	2	--								37							13.5X16.7							
ST491B-II	3	--								42							Ø13.5							
ST209-1 1/8	1	--								37							13.5X16.7							
ST209-1 1/8-I	2	29.927	--							127	98	42.8			37	60	57.547			7	127	13.5X16.7	31850	17500
ST209-1 1/8-II	3	--	42												Ø13.5									
ST209-1 1/8	1	--	37	13.5X16.7																				
ST209-1 1/8-I	2	29.927	--	127	98	42.8							42	60	57.547							7		
ST209-1 1/8-II	3	--	37										13.5X16.7											
ST209-1 1/8	1	--	42										Ø13.5											
ST209-1 1/8-I	2	29.927	--				127	98	42.8				37			60	57.547	7	127	13.5X16.7	31850			
ST209-1 1/8-II	3	--	42										Ø13.5											
ST209-1 1/8	1	--	37										13.5X16.7											
ST209-1 1/8-I	2	29.927	--										127	98	42.8					42		60		
ST209-1 1/8-II	3	--	37							13.5X16.7														
ST209-1 1/8	1	--	42							Ø13.5														
ST209-1 1/8-I	2	29.927	--							127	98	42.8				37	60	57.547	7	127			13.5X16.7	31850
ST209-1 1/8-II	3	--	42	Ø13.5																				
ST209-1 1/8	1	--	37	13.5X16.7																				
ST209-1 1/8-I	2	29.927	--	127	98	42.8										42						60	57.547	
ST209-1 1/8-II	3	--	37				13.5X16.7																	
ST209-1 1/8	1	--	42				Ø13.5																	
ST209-1 1/8-I	2	29.927	--				127	98	42.8							37	60	57.547	7	127	13.5X16.7			
ST209-1 1/8-II	3	--	42										Ø13.5											
ST209-1 1/8	1	--	37										13.5X16.7											
ST209-1 1/8-I	2	29.927	--										127	98	42.8	42					60	57.547	7	
ST209-1 1/8-II	3	--	37							13.5X16.7														
ST209-1 1/8	1	--	42							Ø13.5														
ST209-1 1/8-I	2	29.927	--							127	98	42.8				37	60	57.547	7	127				13.5X16.7
ST209-1 1/8-II	3	--	42	Ø13.5																				
ST209-1 1/8	1	--	37	13.5X16.7																				
ST209-1 1/8-I	2	29.927	--	127	98	42.8										42					60	57.547	7	127
ST209-1 1/8-II	3	--	37				13.5X16.7																	
ST209-1 1/8	1	--	42				Ø13.5																	
ST209-1 1/8-I	2	29.927	--				127	98	42.8							37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42										Ø13.5											
ST209-1 1/8	1	--	37										13.5X16.7											
ST209-1 1/8-I	2	29.927	--										127	98	42.8	42					60	57.547	7	127
ST209-1 1/8-II	3	--	37							13.5X16.7														
ST209-1 1/8	1	--	42							Ø13.5														
ST209-1 1/8-I	2	29.927	--							127	98	42.8				37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42	Ø13.5																				
ST209-1 1/8	1	--	37	13.5X16.7																				
ST209-1 1/8-I	2	29.927	--	127	98	42.8										42					60	57.547	7	127
ST209-1 1/8-II	3	--	37				13.5X16.7																	
ST209-1 1/8	1	--	42				Ø13.5																	
ST209-1 1/8-I	2	29.927	--				127	98	42.8							37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42										Ø13.5											
ST209-1 1/8	1	--	37										13.5X16.7											
ST209-1 1/8-I	2	29.927	--										127	98	42.8	42					60	57.547	7	127
ST209-1 1/8-II	3	--	37							13.5X16.7														
ST209-1 1/8	1	--	42							Ø13.5														
ST209-1 1/8-I	2	29.927	--							127	98	42.8				37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42	Ø13.5																				
ST209-1 1/8	1	--	37	13.5X16.7																				
ST209-1 1/8-I	2	29.927	--	127	98	42.8										42					60	57.547	7	127
ST209-1 1/8-II	3	--	37				13.5X16.7																	
ST209-1 1/8	1	--	42				Ø13.5																	
ST209-1 1/8-I	2	29.927	--				127	98	42.8							37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42										Ø13.5											
ST209-1 1/8	1	--	37										13.5X16.7											
ST209-1 1/8-I	2	29.927	--										127	98	42.8	42					60	57.547	7	127
ST209-1 1/8-II	3	--	37							13.5X16.7														
ST209-1 1/8	1	--	42							Ø13.5														
ST209-1 1/8-I	2	29.927	--							127	98	42.8				37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42	Ø13.5																				
ST209-1 1/8	1	--	37	13.5X16.7																				
ST209-1 1/8-I	2	29.927	--	127	98	42.8										42					60	57.547	7	127
ST209-1 1/8-II	3	--	37				13.5X16.7																	
ST209-1 1/8	1	--	42				Ø13.5																	
ST209-1 1/8-I	2	29.927	--				127	98	42.8							37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42										Ø13.5											
ST209-1 1/8	1	--	37										13.5X16.7											
ST209-1 1/8-I	2	29.927	--										127	98	42.8	42					60	57.547	7	127
ST209-1 1/8-II	3	--	37							13.5X16.7														
ST209-1 1/8	1	--	42							Ø13.5														
ST209-1 1/8-I	2	29.927	--							127	98	42.8				37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42	Ø13.5																				
ST209-1 1/8	1	--	37	13.5X16.7																				
ST209-1 1/8-I	2	29.927	--	127	98	42.8										42					60	57.547	7	127
ST209-1 1/8-II	3	--	37				13.5X16.7																	
ST209-1 1/8	1	--	42				Ø13.5																	
ST209-1 1/8-I	2	29.927	--				127	98	42.8							37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42										Ø13.5											
ST209-1 1/8	1	--	37										13.5X16.7											
ST209-1 1/8-I	2	29.927	--										127	98	42.8	42					60	57.547	7	127
ST209-1 1/8-II	3	--	37							13.5X16.7														
ST209-1 1/8	1	--	42							Ø13.5														
ST209-1 1/8-I	2	29.927	--							127	98	42.8				37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42	Ø13.5																				
ST209-1 1/8	1	--	37	13.5X16.7																				
ST209-1 1/8-I	2	29.927	--	127	98	42.8										42					60	57.547	7	127
ST209-1 1/8-II	3	--	37				13.5X16.7																	
ST209-1 1/8	1	--	42				Ø13.5																	
ST209-1 1/8-I	2	29.927	--				127	98	42.8							37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42										Ø13.5											
ST209-1 1/8	1	--	37										13.5X16.7											
ST209-1 1/8-I	2	29.927	--										127	98	42.8	42					60	57.547	7	127
ST209-1 1/8-II	3	--	37							13.5X16.7														
ST209-1 1/8	1	--	42							Ø13.5														
ST209-1 1/8-I	2	29.927	--							127	98	42.8				37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42	Ø13.5																				
ST209-1 1/8	1	--	37	13.5X16.7																				
ST209-1 1/8-I	2	29.927	--	127	98	42.8										42					60	57.547	7	127
ST209-1 1/8-II	3	--	37				13.5X16.7																	
ST209-1 1/8	1	--	42				Ø13.5																	
ST209-1 1/8-I	2	29.927	--				127	98	42.8							37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42										Ø13.5											
ST209-1 1/8	1	--	37										13.5X16.7											
ST209-1 1/8-I	2	29.927	--										127	98	42.8	42					60	57.547	7	127
ST209-1 1/8-II	3	--	37							13.5X16.7														
ST209-1 1/8	1	--	42							Ø13.5														
ST209-1 1/8-I	2	29.927	--							127	98	42.8				37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42	Ø13.5																				
ST209-1 1/8	1	--	37	13.5X16.7																				
ST209-1 1/8-I	2	29.927	--	127	98	42.8										42					60	57.547	7	127
ST209-1 1/8-II	3	--	37				13.5X16.7																	
ST209-1 1/8	1	--	42				Ø13.5																	
ST209-1 1/8-I	2	29.927	--				127	98	42.8							37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42										Ø13.5											
ST209-1 1/8	1	--	37										13.5X16.7											
ST209-1 1/8-I	2	29.927	--										127	98	42.8	42					60	57.547	7	127
ST209-1 1/8-II	3	--	37							13.5X16.7														
ST209-1 1/8	1	--	42							Ø13.5														
ST209-1 1/8-I	2	29.927	--							127	98	42.8				37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42	Ø13.5																				
ST209-1 1/8	1	--	37	13.5X16.7																				
ST209-1 1/8-I	2	29.927	--	127	98	42.8										42					60	57.547	7	127
ST209-1 1/8-II	3	--	37				13.5X16.7																	
ST209-1 1/8	1	--	42				Ø13.5																	
ST209-1 1/8-I	2	29.927	--				127	98	42.8							37	60	57.547	7	127				
ST209-1 1/8-II	3	--	42										Ø13.5											
ST209-1 1/8	1	--	37										13.5X16.7											
ST209-1 1/8-I	2																							

211系列

轴承型号	类型	内径尺寸 (mm)		基本尺寸 (mm)								基本额定载荷 (N)		
		H (SQ)	d (RD)	L	P	B	A	F	do	E	C	N(N1XN2)	动载荷 Cr	静载荷 Cor
DHU55R-211	1	--	55	139.7	113.5	51	46.4	73	69	9	139.7	13.5X15.1	43550	25000
DHU55R-211-I	2	--					42	71		8		Ø13.5		
ST211-1 3/4	1	--	45.212				46.4	73		9		Ø13.5		
ST211-2 3/16	1	--	55.575				42	71		8		Ø13.5		
ST211-2 3/16-I	2	--	--				46.4	73		9	139.7	13.5X15.1		
DHU40S-211	1	40.878	--			51	46.4	73		8		Ø13.5		
FD211-1 1/2	2	38.89	--				42	71		8		Ø13.5		