



SA200(轻系列)
带偏心套外球面球轴承



CSA200
带偏心套外圆柱面球轴承



SA200G
可再润滑型



H型密封



J型密封

SA200 CSA200 系列

轴承 型号	轴 径		基本尺寸(mm)										基本额定载荷 (N)		重量 (kg)	
	d		D	B	C	S	B ₁	B ₂	d ₁	G	ds		Ca	动载荷 C _r		静载荷 C _{0r}
	(in)	(mm)									(mm)	(in,UNF)				
SA 201		12									M6x1					
201-8	1/2		40	19.1	12	6	28.6	13.5	28.6	5		1/4-28	3.5	9550	4780	0.2
SA 202		15									M6x1					
202-9	9/16		40	19.1	12	6	28.6	13.5	28.6	5		1/4-28	3.5	9550	4780	0.2
202-10	5/8															
SA 203		17									M6x1					
203-11	11/16		40	19.1	12	6	28.6	13.5	28.6	5		1/4-28	3.5	9550	4780	0.2
SA 204		20									M6x1					
204-12	3/4		47	21.5	14	7	31	13.5	33.3	5		1/4-28	4	12820	6650	0.21
SA 205		25									M6x1					
205-13	13/16															
205-14	7/8		52	22	15	7.5	31.5	13.5	38.1	5		1/4-28	4.3	14030	8050	0.25
205-15	15/16															
205-16	1															
SA 206		30									M6x1					
206-17	1-1/16															
206-18	1-1/8		62	23.8	16	8	35.7	15.9	44.5	6		1/4-28	4.9	19470	11430	0.39
206-19	1-3/16															
206-20	1-1/4															
SA 207		35									M8x1					
207-20	1-1/4															
207-21	1-5/16		72	25.4	17	8.5	38.9	17.5	55.6	6.5		5/16-24	5.5	25690	15550	0.6
207-22	1-3/8															
207-23	1-7/16															
SA 208		40									M8x1					
208-24	1-1/2		80	30.2	18	9	43.7	18.3	60.3	6.5		5/16-24	6	29510	18140	0.77
208-25	1-9/16															
SA 209		45									M8x1					
209-26	1-5/8		85	30.2	19	9.5	43.7	18.3	63.5	6.5		5/16-24	6.1	31850	20800	0.84
209-27	1-11/16															
209-28	1-3/4															
SA 210		50									M8x1					
210-30	1-7/8		90	30.2	20	10	43.7	18.3	69.9	6.5		5/16-24	6.6	34990	23700	1.02
210-31	1-15/16															
210-32	2															
SA 211		55									M10x1.25					
211-32	2		100	32.5	21	10.5	48.4	20.7	76.2	8		3/8-24	7.2	43340	29390	1.37
211-33	2-1/16															
211-34	2-1/8															
211-35	2-3/16															
SA 212		60									M10x1.25					
212-36	2-1/4		110	37.2	22	11	53.1	22.3	84.2	8		3/8-24	7.5	47680	33430	1.85
212-37	2-5/16															
212-38	2-3/8															
212-39	2-7/16															

备注：1) 后缀G=外圈带油槽和油孔。

2) 后缀N=非润滑型，不带油槽和油孔，不带定位钉和定位钉孔。